



# VERTICAL SPLIT-CASE PUMPS




Starlone

FIRE PUMP SINGAPORE PTE LTD

No.8 Keng Chin Road  
#13-11 Cyan South Tower  
Singapore 258710

Phone +65 6515 5123  
Fax +65 6515 5272  
Saha +65 90998565





## ABOUT FIRE PUMP SINGAPORE (FPS)

FPS, with its 20 years of experience has always been a progressive organization that has remained in the forefront of the Fire Fighting Industry with innovative, unconventional, environmental friendly, re-engineered and unique products.

FPS in its state-of-the-art manufacturing plants in **China** works in close connections with renowned governmental and certification bodies to provide key answers to the challenges faced by the society.

FPS brings together over 2-Decades of expertise and experience in form of **Design, Consultancy, Manufacturing, Supply, Installation, Testing, Commissioning, Maintenance & Refurbishment** of fire protection and fire fighting systems.



# FPS CERTIFIED FACILITY FOR FIRE PUMP SYSTEMS

## TESTING FACILITY AND ASSEMBLY LINE

FPS has established a fully equipped AS2941 Pump Testing facility with advance testing and calibration devices that enable to accurately inspect and test the operation of each Centrifugal Stationery Fire Pump to the required level of compliance standard as per AS2941.

The Fire Pumps then undergo various processes in our modern well organized manufacturing and assembly line.

Before delivering to our customers, each pump undergoes necessary inspection, tests and production control, during the Assembly process, for which all records are maintained.

## PERFORMANCE TESTS

Performance curves are plotted within the FPS AS2941 **Approved Pump Testing Facility** showing the Efficiency, Break-Horsepower(kw), and Total Head developed at shutoff, at rated capacity, at 150%of rated capacity, and at selected intermediate capacities between shutoff and maximum capacities exceeding 150% of rated capacity.



# FPS CERTIFIED FACILITY FOR FIRE PUMP SYSTEMS

## HYDROSTATIC TEST

Each pump is to be tested hydro-statically for not less than 5 minutes. The test pressure is to be up to 2 times the maximum working pressure of the pump, but in no case less than 250psi (1724 kPa) to ensure no rupture or leakage through the castings at the test pressure.

## IMPELLER BALANCING

The impellers of each pump shall be dynamically balanced to the G6.3 balance quality grade in accordance with the requirements for pump impellers in the Standard for Mechanical Vibration -Balance Quality.





# VERTICAL SPLIT-CASE PUMPS

## *DESIGN & OPERATION FEATURES*

Excellent hydraulic performance, high efficiency, good cavitation performance.

Staggered vane construction for changing the rate of impeller through pump tongue, which decrease the liquid pulse 1%~4% of the head, more stable flow, higher efficiency, less vibration, working more steady.

For casing, using ANSYS for optimizing structure, high-intensity.

For bearing, with short span, thicken shaft, which makes small deflection when rotator running, and works more stable.

The shaft is full sealing no touch with liquid, bearing parts are oil lip sealing and V-type sealing ring, which protect against leaking, dust, water and humidity.

Pump inlet and outlet flange could be by ISO, DIN, BS, ANSI, KS standards etc.

Bearing lubrication, grease for standard, oil for customized.

Shaft sealing is packing seal interchangeable with single end surface seal, or mechanical seal, double seal or flushing system by standard API682.

Bearing is assembled with interface for testing temperature and vibration, convenient for remote control.


Except pump casing, cover, impeller etc, the other parts is modular designed and standardize; bearing, sealing part, shaft sleeve are all could be interchangeable.

Pump rotation is clockwise from driven.




# VERTICAL SPLIT-CASE PUMPS

## *SPECIAL FEATURES AND PERFORMANCE ANALYSIS*



Staggered vane construction creates more stable flow and decreases pressure pulsation.

Double curvature, streamline inlet, high efficiency, good cavitation performance.



Analyzing by CFD, pump efficiency is improved to 92%.



# VERTICAL SPLIT-CASE PUMPS

## *PERFORMANCE RANGE*

Capacity	: 100~30000m <sup>3</sup> /h
Head	: 7~220m
Efficiency	: 92%
Power	: 15~4000kW
Inlet Dia.	: 150~1600mm
Outlet Dia.	: 100~1400mm
Working Pressure	: ≤2.5MPa
Temperature	: -20℃~80 °C





## APPLICATIONS

Power industry  
Papermaking industry  
Iron and steel industry  
The petrochemical industry  
Water industry  
Desalination of sea water



# HORIZONTAL SPLIT-CASE PUMPS

## SECTIONAL DRAWING



- |                |                |                   |                   |
|----------------|----------------|-------------------|-------------------|
| 1, Baseplate   | 2, Pump casing | 3, Shield         | 4, Coupling parts |
| 5, Bolt        | 6, Wing nut    | 7, Bolt           | 8, I-nut          |
| 9, Headed bolt | 10, I-nut      | 10, Gasket        | 11, Motor base    |
| 12, Bolt       | 13, Bolt       | 14, spring gasket | 15, gasket        |





# VERTICAL SPLIT-CASE PUMPS

## *NOMENCLATURE*

CPS V ### - XXX (M) A / &

---

CPS - standard series code

V - vertical type

### - pump inlet diameter

xxx - impeller nominal diameter

(M) - impeller Type

A - code of cutting of impeller diameter


& - number of poles driving the motor



# VERTICAL SPLIT-CASE PUMPS

*PUMP SELECTION BASED ON FLOW AND PRESSURE - 50Hz*

**Chart 1**






# VERTICAL SPLIT-CASE PUMPS

*PUMP SELECTION BASED ON FLOW AND PRESSURE - 50Hz*

**Chart 2**






# VERTICAL SPLIT-CASE PUMPS

*PUMP SELECTION BASED ON FLOW AND PRESSURE - 60Hz*

**Chart 1**








# VERTICAL SPLIT-CASE PUMPS

*PUMP SELECTION BASED ON FLOW AND PRESSURE - 60Hz*

**Chart 2**






# VERTICAL SPLIT-CASE PUMPS

*PUMP SELECTION BASED ON FLOW AND PRESSURE - 60Hz*

**Chart 3**





# VERTICAL SPLIT-CASE PUMPS

*PUMP SELECTION BASED ON FLOW AND PRESSURE - 60Hz*

**Chart 4**

